



Accurate Technology Services, Inc.
829 Gretel Ave, Concord, NC 28027
1-877-SRG-SRVC(774-7782)
ph: 1-704-784-8287 fax: 1-704-784-8290
www.atssurge.com sales@atssurge.com

ZONE BARRIER SERIES

Part #AT24509



The effective barrier between surges and sensitive I/O ports.

Application: The AT24509 protects RS232 communication links from transients caused by direct or indirect lightning.

Installation: The Zone Barrier series can be mounted on any standard 35mm DIN rail, or any flat surface. Ground wire is required for surface mounted applications and will be included with purchase.

Technology: High energy metal oxide varistors are combined with a double network of ultra fast diodes and silicon avalanche diodes to form three distinct stages of protection.

Approval: UL497A listed, tested to IEC801-5, CCITT K17

SPECIFICATIONS

Circuit Type: 3 Stage Series Hybrid
Lines Protected: 4 + Shield
Connectors: 5 Pos. Terminal Strip
Surge Capacity: 3kA 8/20 impulse
Clamp Voltage: 27V @ 2kA 8/20
Rated Voltage: 15Vdc
Max Frequency: 0-5MHz
Max Load Current: 0.5 Amperes
Case Dimensions: 5.1" x 2.3" x 1.0" overall

Clamping Voltage measured between a pair during the common mode application of 2kV (1.2-50 μ s) 1kA (8/20 μ s) waveform

