




























CURRENT RATING	TYPE	2 POLE - 2 WIRE NO GROUND		2 POLE - 3 WIRE GROUNDING		3 POLE 4 WIRE GROUNDING
		125V	250V	125V	250V	125/250V
15A	STRAIGHT BLADE	 1-15R	 2-15R	 5-15R	 6-15R	
	TWIST-LOCK	 L1-15R		 L5-15R	 L6-15R	
20A	STRAIGHT BLADE		 2-20R	 5-20R	 6-20R	 14-20R
	TWIST-LOCK		 L2-20R	 L5-20R	 L6-20R	 L14-20R
30A	STRAIGHT BLADE		 2-30R	 5-30R	 6-30R	 14-30R
	TWIST-LOCK			 L5-30R	 L6-30R	 L14-30R
50A	STRAIGHT BLADE			 5-50R	 6-50R	 14-50R
	TWIST-LOCK					 CS6364/65
60A	STRAIGHT BLADE					 14-60R
	TWIST-LOCK					

- NOTES: 1) Female receptacles shown. For male plug change suffix from "R" to "P" and mirror image.
2) For female connectors change suffix from "R" to "C".
3) Twist-lock 50A CS6364 connector and CS6365 plug are not NEMA.
4) Normally G = ground (green), W = neutral (white), X & Y = hot (red & black).